

POWDER TYPE FIRE EXTINGUISHER (MAP 40%)

RESGUARDO[®]

Dry chemical powder (Mono Ammonium Phosphate) is a multi-purpose fire extinguisher, quick in action with in built pressure gauge indicating readiness for use.



IS : 15683 : 2018



CML No 4749785



Capacity	1 Kg	2 Kg	4 Kg	6 Kg	9 Kg
MAP Content	40%	40%	40%	40%	40%
Fire Rating	1A 21B	1A 34B	2A 55B	3A 89B	4A 144B
Diameter (MM)	85±0.5	107±0.5	140±0.5	160±0.5	174±0.5
Total Height (MM)	330	383	449	492	592
Empty weight (KG) Approx.	1.1	1.3	2	2.4	3.1
Full weight (KG) Approx.	2.1	3.3	6	8.4	12.1
Avg. Effective Discharge Time	08 SEC.	10 SEC.	14 SEC.	20 SEC.	23 SEC.
Operating temperature	-20°C TO +60°C	-20°C TO +60°C	-20°C TO +60°C	-20°C TO +60°C	-20°C TO +60°C
Service Pressure	15 bar	15 bar	15 bar	15 bar	15 bar
Maximum Service Pressure	16.5 bar	16.5 bar	16.5 bar	16.5 bar	16.5 bar
Test Pressure	35 bar	35 bar	35 bar	35 bar	35 bar

POWDER TYPE FIRE EXTINGUISHER (MAP 90%)

Dry chemical powder (Mono Ammonium Phosphate) is a multi-purpose fire extinguisher, quick in action with in built pressure gauge indicating readiness for use.



IS : 15683 : 2018



CML No 4749785



Capacity	1 Kg	2 Kg	4 Kg	6 Kg	9 Kg
MAP Content	90%	90%	90%	90%	90%
Fire Rating	1A 21B	2A 34B	3A 89B	4A 144B	6A 233B
Diameter (MM)	85±0.5	107±0.5	140±0.5	160±0.5	174±0.5
Total Height (MM)	330±1	383±1	449±1	492±1	592
Empty weight (KG) Approx.	1	1.2	2	2.3	3
Full weight (KG) Approx.	2	3.2	6	8.3	12
Avg. Effective Discharge Time	08 SEC.	10 SEC.	14 SEC.	20 SEC.	23 SEC.
Operating temperature	-20°C TO +60°C	-20°C TO +60°C	-20°C TO +60°C	-20°C TO +60°C	-20°C TO +60°C
Service Pressure	15 bar	15 bar	15 bar	15 bar	15 bar
Maximum Service Pressure	16.5 bar	16.5 bar	16.5 bar	16.5 bar	16.5 bar
Test Pressure	35 bar	35 bar	35 bar	35 bar	35 bar

